

Lynar

Technical Overview



	RI Recessed trim-less	RV Recessed visible trim	C/S Ceiling / Suspended	SDI Suspended Direct / Indirect
Indirect luminaire luminous flux/m	-	-	-	990 lm/m (DALI)
LED colour	-	-	-	827, 830, 835, 840, 930, 940
Electrical connection	48Vdc (not included, order separately)	48Vdc (not included, order separately)	48Vdc (not included, order separately)	48Vdc (not included, order separately)
Colour	D	2	1 2 3 6 9 +	1 2 3 6 9 +
Dimensions	L: 500- 3000 mm	L: 500 - 3000 mm	L: 500 - 3000 mm	L: 1000 - 3000 mm SH (mm): 1500, 3000, 5000

* The inner part of the profile is always black

 ≥ 95 %	GR0	GR1	CASAMBI		 WARRANTY		
------------	-----	-----	---------	--	--------------	--	--

Linear extruded aluminium profile system with integrated 48V track. Indirect light option with SOP diffuser. Wide range of light insets (linear, spot, pendant). Power supply can be mounted remotely (PSE) or inside the profile (PSI).

Sistema lineare in alluminio estruso con binario 48V integrato. Disponibile con luce indiretta con schermo SOP. Ampia gamma di lampade installabili (lineari, spot, pendenti). Il trasformatore può essere installato remoto (PSE) o all'interno del profilo (PSI).

Système de profilés linéaires en aluminium extrudé avec rail 48V intégré. Option lumière indirecte avec diffuseur SOP. Large gamme d'encarts lumineux (linéaire, spot, suspension). L'alimentation peut être montée à distance (PSE) ou à l'intérieur du profilé (PSI).

Spot insets

	Atos LYN Luminaire luminous flux: Up to 2x1050 lm Beam angle: 18°, 20°, 25°, 30°, 50°, 59°, 28°- 46° LED colour: 827, 830, 840, 927, 930, 935, 940 Spots: 1x / 2x Driver: DALI Diameter: 26, 32, 45 mm
--	---

	Eye LYN Luminaire luminous flux: Up to 1400 lm Beam angle: 10°, 22°, 26°, 30°, 45°, 46°, 22 - 45° LED colour: 927, 930, 935, 940 Driver: DALI Diameter: 60 mm
--	--

Pendant insets

	Biba LYN Luminaire luminous flux: Up to 936 lm Beam angle: 42°, 62° LED colour: 830, 840, 927, 930, 935, 940 Driver: DALI Diameter: 75 mm
--	--

	Pipes 45 S LYN Luminaire luminous flux: Up to 1300 lm Beam angle: 42°, 62° LED colour: 830, 840, 927, 930, 935, 940 Driver: DALI Diameter: 45 mm
--	---

	Pixy LYN Luminaire luminous flux: Up to 1532 lm Beam angle: 30°, 50° LED colour: 830, 840, 927, 930, 935, 940 Driver: DALI
--	---

	Zoe LYN Luminaire luminous flux: Up to 1481 lm, 12W LED colour: 830, 840, 927, 930, 935, 940 Driver: DALI
--	--

Linear insets

	Kalis 36 LYN Luminaire luminous flux: Up to 1600lm Module length: 285 mm - 1405 mm Optic: SOP, DPR LED colour: 827, 830, 835, 840, 930, 940 Driver: DALI
--	---

	Rylo LYN Luminaire luminous flux: 60 - 130 lm/spot Module length: 143 mm - 843 mm (4x - 24x spot) Beam angle: 22°, 30°, 50°, Asymmetric LED colour: 927, 930, 935, 940 Driver: DALI
--	--

Corner profiles

	Horizontal corner 90° and 135° Integrated PWR connection module Dimension: 50x50 mm
--	---

	Vertical corner 90° Integrated PWR connection module Dimension: 50x50 mm
--	--

Power supply

	PSE - power supply external PWR supply position: Integrated in the ceiling cup PWR supply type: 48V constant voltage driver
--	--

	PSI - power supply internal PWR supply position: Integrated in the profile inset PWR supply type: 48V constant voltage driver
--	--