

Pipes R

Technical Overview



RI

Recessed trim-less



Ø 60, H 71 mm
Fixed

RV

Recessed visible trim



Ø 60, H 70 / 103 mm
Fixed / Adjustable

RVS / RVSQ

Recessed visible trim



Ø 65, H 69 / 102 mm
Fixed / Adjustable



Ø 80, H 82 mm
Fixed



Ø 80, H 82 / 115 mm
Fixed / Adjustable



Ø 89, H: 82 / 115 mm
Fixed / Adjustable



Ø 85, H 82 / 115 mm
RVSQ Fixed / Adjustable



Ø 100, H 116 / 126 mm
Fixed / Adjustable



Ø 105, H 133 mm
Adjustable



Ø 115, H 133 mm
Adjustable



Ø 133, H 175 mm
Fixed



Ø 140, H 189 mm
Adjustable

SPOT/SLOT



Ø 85, H 70 mm
RVS SPOT Fixed



Ø 85, H 105 mm
RVS SLOT Adjustable

	60-65 MM	85 MM	80-89 MM	100-115 MM	140 MM
Beam angle	20°, 30°, 55°	20°	20°, 30°, 55°	19°, 30°, 40°, 60°	15°, 24°, 30°, 40°, 56°, 62°
Orientation	25° (A) / 360°	25° (Slot) / 360°	25° (A) / 360°	±25° (A) / 360°	±25° (A) / 360°
Luminaire luminous flux	up to 1050 (20°, 30°), 1400 lm (55°)	up to 740 lm	up to 1050 (20°, 30°), 1400 lm (55°)	950 - 3400 lm	1300 - 6500 lm
LED colour	830, 840, 927, 930, 935, 940	830, 840, 927, 930, 935, 940	830, 840, 927, 930, 935, 940	830, 835, 840, 927, 930, 940	830, 835, 840, 927, 930, 940
Dynamic light	Dim to warm (D2W)	Dim to warm (D2W)	Dim to warm (D2W)	Tunable white 2700 - 6500K (TW)	Tunable white 2700 - 6500K (TW)
Special LED colour	-	-	-	Alaska, Clear white, Fresh rose, Warm crispy, Warm vivid, Plant white	Alaska, Clear white, Fresh rose, Warm crispy, Warm vivid, Plant white
Driver	Casambi, DALI, FO	Casambi, DALI, FO	Casambi, DALI, FO	Casambi, DALI, FO	Casambi, DALI, FO
Driver position	Remote	Remote	Remote	Remote	Remote
IP protection	IP20, IP44* (RV, RVS)	IP20	IP20	IP20, IP44* (RV)	IP20
Colour	1 2 3	1 2 3	1 2 3	1 2 3	1 2 3

*IP value from the exposed side

≥ 85 %

TW

D2W

VIVID

GR0

GR1

7 year WARRANTY

Light source: High-power COB LED, CRI>80/90, MacAdam≤2, 50.000h L90 B10 at 35°C. **Optic:** Highly efficient with uniform distribution, metalized polycarbonate with lacquer finish. **Body:** Polycarbonate. **Control gear:** Constant current driver order separately. **Power supply:** 150 - 1050mA.

Sorgente: High-power COB LED, CRI>80/90, MacAdam≤2, 50.000h L90 B10 a 35°C. **Ottica:** Ottica ad alta efficienza con distribuzione uniforme, polycarbonato metallizzato tramite laccatura. **Corpo:** Polycarbonato. **Alimentazione:** Alimentatore a corrente costante - ordinare separatamente. **Alimentatore:** 150 - 1050mA.

Source de luminaire: Module COB LED haute puissance, IRC> 80/90, MacAdam ≤ 2, 50.000h, L90 B10. **Optique:** Haute efficacité avec une distribution uniforme, polycarbonate métallisé avec finition laquée. **Corps:** Polycarbonate. **Alimentation:** Driver à courant constant - à commander séparément. **Alimentation:** 150 - 1050mA.