

Atom Track

Designed by LedsC4 Architectural



+ Atom

Low Voltage P. 136 / Ceiling P. 320 / Spotlight P. 324

Versatile collection for ambivalent spaces Collection polyvalente pour les espaces ambivalents

Simplicity always wins. Atom's three-phase track projector option is a popular choice among designers seeking to create ambivalent spaces requiring quality lighting with great versatility thanks to the wide choice of lenses, installations and accessories in the collection. La simplicité est toujours un atout. L'option de projecteur sur rail triphasé Atom est un choix récurrent des concepteurs dans la création d'espaces ambivalents qui nécessitent un éclairage de qualité et très polyvalent grâce au grand nombre d'optiques, d'installations et d'accessoires disponibles dans la collection.




Atom Track

BODY MAT	50000h	3
AL	L80 B20	MacAdam

Atom Track 52 LED AC


IP	DIF MAT		WELL					120V
20	PC			320°	90°			<input type="radio"/> 14 <input checked="" type="radio"/> 60



LED						
K	CRI	W Total	Real Lm	Optics	Code	
3000	90	7.5	245	24°	35-6276	
3000	90	7.5	308	32°	35-6277	- 14 - ML PHASE CUT 120V
3000	90	7.5	325	42°	35-6278	- 60 - ML PHASE CUT 120V

Atom Track 75 LED AC


IP	DIF MAT		WELL					120V
20	PC			320°	90°			<input type="radio"/> 14 <input checked="" type="radio"/> 60



LED						
K	CRI	W Total	Real Lm	Optics	Code	
3000	90	14.3	692	22°	35-6282	
3000	90	14.3	870	31°	35-6283	- 14 - ML PHASE CUT 120V
3000	90	14.3	916	38°	35-6284	- 60 - ML PHASE CUT 120V

Atom Track 97 LED AC

IP	DIF MAT		WELL					120V
20	PC			90°	320°			<input type="radio"/> 14 <input checked="" type="radio"/> 60



LED						
K	CRI	W Total	Real Lm	Optics	Code	
3000	90	31	1269	24°	35-6288	
3000	90	31	1595	36°	35-6289	- 14 - ML PHASE CUT 120V
3000	90	31	1679	43°	35-6290	- 60 - ML PHASE CUT 120V

Atom Track 52 LED AC

Atom Track 75 LED AC


Atom Track 97 LED AC

Lens accessories


Accessoires optiques

	Elliptical diffuser (5u.) Diffuseur elliptique (5 u.)		71-6274-00-00	71-6280-00-00	71-6286-00-00
	Halo fader (5u.) Diffuseur de halo (5 u.)		71-6275-00-00	71-6281-00-00	71-6287-00-00
	Visual comfort (1u.) Confort visuel (1 u.)	60 <input checked="" type="radio"/>	71-6276-60-00	71-6282-60-00	71-6288-60-00
	Honeycomb panel (5u.) Grille en nid d'abeille (5 u.)	60 <input checked="" type="radio"/>	71-6273-60-00	71-6279-60-00	71-6285-60-00
	Visor Visière	60 <input checked="" type="radio"/>	71-6277-60-00	71-6283-60-00	71-6289-60-00
	Anti-glare flaps Ailettes anti-éblouissement	14 <input type="radio"/>	-	-	71-6290-14-00
		60 <input checked="" type="radio"/>	-	-	71-6290-60-00
	Front ring Anneau frontal	14 <input type="radio"/>	71-6436-14-00	71-6437-14-00	71-6438-14-00
		23 <input checked="" type="radio"/>	71-6436-23-00	71-6437-23-00	71-6438-23-00

Atom Track 52 LED Driver



○ ●
14 60




LED									
K	CRI	W Total	Real Lm	Optics	Code				
2700	90	10.5	428	8°	35-A021	- 14 -	- OS -	ON-OFF 220-240V	
								- 60 -	- ES -
2700	90	15	1106	20°	35-7287	- 14 -	- OS -		
								- 60 -	- ES -
2700	90	15	1230	34°	35-7288	- 14 -	- OS -		
								- 60 -	- XB -
2700	90	15	1234	45°	35-7289	- 14 -	- OS -		
								- 60 -	- ES -
3000	90	10.5	437	8°	35-A022	- 14 -	- OS -		
								- 60 -	- ES -
3000	90	15	1106	20°	35-7290	- 14 -	- OS -		
								- 60 -	- ES -
3000	90	15	1230	34°	35-7291	- 14 -	- OS -		
								- 60 -	- XB -
3000	90	15	1234	45°	35-7292	- 14 -	- OS -		
								- 60 -	- ES -
4000	90	10.5	459	8°	35-A023	- 14 -	- OS -		
								- 60 -	- ES -
4000	90	15	1271	20°	35-A003	- 14 -	- OS -		
								- 60 -	- ES -
4000	90	15	1414	34°	35-A004	- 14 -	- OS -		
								- 60 -	- XB -
4000	90	15	1418	45°	35-A005	- 14 -	- OS -		
								- 60 -	- TW -
2700-6500	90	14	926	23°	35-A066	- 14 -	- OS -		
								- 60 -	- TW -
2700-6500	90	14	1089	38°	35-A067	- 14 -	- OS -		
								- 60 -	- TW -
2700-6500	90	14	1076	49°	35-A068	- 14 -	- OS -		
								- 60 -	- TW -

Atom Track 52 LED Driver Zoom



○ ●
14 60





LED											
K	CRI	W Total	Real Lm	Optics	Code						
2700	90	15	518	Zoom 16°-47°	35-A060	- 14 -	- OS -	ON-OFF 220-240V			
								- 60 -	- ES -	DALI-2 220-240V	
										- 60 -	- XB -
3000	90	15	551	Zoom 16°-47°	35-A061	- 14 -	- OS -	ON-OFF 220-240V			
								- 60 -	- ES -	DALI-2 220-240V	
										- 60 -	- XB -
4000	90	15	577	Zoom 16°-47°	35-A062	- 14 -	- OS -	ON-OFF 220-240V			
								- 60 -	- ES -	DALI-2 220-240V	
										- 60 -	- XB -

Atom Track 75 LED Driver

IP	DIF MAT					
20	PMMA			320	90	LED DRIVER

○ ●
14 60




LED									
K	CRI	W Total	Real Lm	Optics	Code				
2700	90	16	1634	16°	35-A018	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
2700	90	28	2367	23°	35-7305	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
2700	90	28	2291	31°	35-7306	- 14 - 60	ES	DALI-2	220-240V
							XB	CASAMBI	220-240V
2700	90	28	2355	39°	35-7307	- 14 - 60			
							XB	CASAMBI	220-240V
3000	90	16	1667	16°	35-A019	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
3000	90	28	2367	23°	35-7308	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
3000	90	28	2291	31°	35-7309	- 14 - 60	ES	DALI-2	220-240V
							XB	CASAMBI	220-240V
3000	90	28	2355	39°	35-7310	- 14 - 60			
							XB	CASAMBI	220-240V
4000	90	16	1751	16°	35-A020	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
4000	90	28	2722	23°	35-A009	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
4000	90	28	2635	31°	35-A010	- 14 - 60	ES	DALI-2	220-240V
							XB	CASAMBI	220-240V
4000	90	28	2708	39°	35-A011	- 14 - 60			
							XB	CASAMBI	220-240V
2700-6500	92	23.8	2214	21°	35-A051	- 14 - 60			
2700-6500	92	23.8	2090	34°	35-A052	- 14 - 60	TW	DALI DT8	220-240V
2700-6500	92	23.8	2078	46°	35-A053	- 14 - 60			

Atom Track 97 LED Driver

IP	DIF MAT					
20	PMMA			90	320	LED DRIVER

○ ●
14 60



LED									
K	CRI	W Total	Real Lm	Optics	Code				
2700	90	42	3792	20°	35-7323	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
2700	90	42	3574	31°	35-7324	- 14 - 60	ES	DALI-2	220-240V
							XB	CASAMBI	220-240V
2700	90	42	3414	42°	35-7325	- 14 - 60			
							XB	CASAMBI	220-240V
3000	90	42	3792	20°	35-7326	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
3000	90	42	3574	31°	35-7327	- 14 - 60	ES	DALI-2	220-240V
							XB	CASAMBI	220-240V
3000	90	42	3414	42°	35-7328	- 14 - 60			
							XB	CASAMBI	220-240V
4000	90	42	4361	20°	35-A015	- 14 - 60	OS	ON-OFF	220-240V
							ES	DALI-2	220-240V
4000	90	42	4110	31°	35-A016	- 14 - 60	ES	DALI-2	220-240V
							XB	CASAMBI	220-240V
4000	90	42	3926	43°	35-A017	- 14 - 60			
							XB	CASAMBI	220-240V
2700-6500	92	37	3118	22°	35-A077	- 14 - 60			
2700-6500	92	37	2892	32°	35-A078	- 14 - 60	TW	DALI DT8	220-240V
2700-6500	92	37	2212	40°	35-A079	- 14 - 60			

Atom Track 52 LED Driver	Atom Track 52 LED Driver Zoom	Atom Track 75 LED Driver	Atom Track 97 LED Driver

Controllers P. 1166
Contrôleurs

	CASAMBI-DALI	14 ○	71-A243-14-14	-	71-A243-14-14	71-A243-14-14
		60 ●	71-A243-60-60	-	71-A243-60-60	71-A243-60-60

Sensors P. 1001
Capteurs

	Three-phase track multisensor Multicapteur sur rail triphasé	60 ●	35-A075-60-00	-	35-A075-60-00	35-A075-60-00
--	---	------	----------------------	---	----------------------	----------------------

Lens accessories
Accessoires optiques

	Elliptical diffuser (5u.) Diffuseur elliptique (5 u.)		71-6274-00-00	-	71-6280-00-00	71-6286-00-00
	Halo fader (5u.) Diffuseur de halo (5 u.)		71-6275-00-00	-	71-6281-00-00	71-6287-00-00
	Visual comfort (1u.) Confort visuel (1 u.)	14 ○	71-6276-14-00	-	71-6282-14-00	71-6288-14-00
		60 ●	71-6276-60-00	-	71-6282-60-00	71-6288-60-00
	Honeycomb panel (5u.) Grille en nid d'abeille (5 u.)	60 ●	71-6273-60-00	-	71-6279-60-00	71-6285-60-00
	Visor Visière	60 ●	71-6277-60-00	-	71-6283-60-00	71-6289-60-00
	Anti-glare flaps Ailettes anti-éblouissement	14 ○	-	-	-	71-6290-14-00
		60 ●	-	-	-	71-6290-60-00
	Front ring Anneau frontal	14 ○	71-6436-14-00	-	71-6437-14-00	71-6438-14-00
		23 ●	71-6436-23-00	-	71-6437-23-00	71-6438-23-00